

Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

81 Claim 1 (currently amended) A temperature control system for an inkjet printhead assembly, comprising:

a printhead assembly having ink ejection elements energizable by an electrical pulse having an amplitude and pulse width;

a sensor coupled to the printhead assembly for generating a signal representative of the printhead temperature;

a memory device for storing an optimal operating temperature of the printhead derived from current printhead operating parameters, a thermal response model of the printhead assembly and an ejection history of the ejection elements ~~that collectively define a dynamic estimate of the temperature distribution across a predefined portion of the printhead assembly;~~ and

a controller ~~for reading~~ configured to read a nominal operating pulse width, the signal from the sensor, the ~~dynamic estimate~~ optimal operating temperature from the memory device and the printhead operating parameters, ~~the controller calculates for calculating~~ an adjusted pulse width using the nominal operating pulse width, the signal from the sensor and the current printhead operating parameters; and

a firing controller with an ejection sequence sub-controller for selectively controlling the sequence of fire pulses, a firing delay sub-controller for reducing electromagnetic interference in the printhead assembly and a fractional delay sub-controller for compensating for scan axis directionality errors of the printhead assembly

~~wherein the controller uses the adjusted pulse width to control printhead temperature.~~

Claim 2 (currently amended) A method of controlling the temperature of an inkjet printhead having ink ejection elements, the method comprising:

~~reading~~ sensing a nominal printhead operating temperature;

~~obtaining~~ determining an optimal operating temperature of the printhead derived from a thermal response model of the printhead, ~~and~~ an ejection history of the

CS
ink ejection elements ~~that collectively define a dynamic estimate of the temperature distribution across a predefined portion of the printhead and a current printhead operating temperature using a sensor on the printhead; and~~

~~controlling the temperature of the printhead using the dynamic estimate and the measured temperature of the printhead; and~~

controlling the sequence of fire pulses, reducing electromagnetic interference in the printhead assembly and compensating for scan axis directionality errors of the printhead assembly with a firing controller.

Claim 3 (previously added) The temperature control system of claim 1 wherein the controller is located on at least one of the printhead or externally on a printer.

Claim 4 (previously added) The temperature control system of claim 1 wherein the controller reads the nominal operating pulse width and the pulse width calibration data from a memory located on the printhead assembly.

Claim 5 (previously added) The temperature control system of claim 1 wherein the controller reads the nominal operating pulse width and the pulse width calibration data from a memory located on the printer.

Claim 6 (previously added) The temperature control system of claim 1 wherein the temperature sensor is an analog temperature sensor.

Claim 7 (previously added) The temperature control system of claim 6 further including an analog to digital converter for generating a digital format of the measured analog signal.

Claim 8 (previously added) The temperature control system of claim 1 wherein the temperature sensor is a digital temperature sensor.

Claim 9 (previously added) The temperature control system of claim 1 wherein the temperature sensor includes multiple temperature sensors distributed

around the printhead so as to provide a global measurement of the printhead temperature.

Claim 10 (previously added) The temperature control system of claim 1 wherein the pulse width calibration data is in the form of an equation.

Claim 11 (previously added) The temperature control system of claim 1 wherein the pulse width calibration data is in a look-up table.

Claim 12 (currently amended) A method of controlling the temperature of an inkjet printhead having ink ejection elements energizable by an electrical pulse having an amplitude and pulse width, comprising:

reading a nominal printhead operating temperature, a nominal operating pulse width and pulse width calibration data;

~~obtaining~~ determining an optimal operating temperature of the printhead derived from a thermal response model of the printhead, and an ejection history of the ink ejection elements ~~that collectively define a dynamic estimate of the temperature distribution across a predefined portion of the printhead and a current printhead operating temperature using a sensor on the printhead;~~

determining a pulse width adjustment factor based on the pulse width calibration data, the ~~dynamic estimate~~ optimal operating temperature and the measured temperature of the printhead;

calculating an adjusted operating pulse width based on the pulse width adjustment factor and the nominal operating pulse width; ~~and~~

applying the adjusted operating pulse width to the printhead to control printhead temperature; and

controlling the sequence of fire pulses, reducing electromagnetic interference in the printhead assembly and compensating for scan axis directionality errors of the printhead assembly with a firing controller.

Claim 13 (previously added) The method of controlling the temperature of claim 12 wherein the controller is located on the printhead.

CS
Went

Claim 14 (previously added) The method of controlling the temperature of claim 12 wherein the controller is located on a printer.

Claim 15 (previously added) The method of controlling the temperature of claim 12 wherein the controller reads the nominal operating pulse width and the pulse width calibration data from a memory located on the printhead assembly.

Claim 16 (previously added) The method of controlling the temperature of claim 12 wherein the controller reads the nominal operating pulse width and the pulse width calibration data from a memory located on the printer.

Claim 17 (previously added) The method of controlling the temperature of claim 12 wherein the temperature sensor is an analog temperature sensor.

Claim 18 (previously added) The method of controlling the temperature of claim 17 further including an analog to digital converter for generating a digital format of the measured analog signal.

Claim 19 (previously added) The method of controlling the temperature of claim 12 wherein the temperature sensor is a digital temperature sensor.

Claim 20 (previously added) The method of controlling the temperature of claim 12 wherein the temperature sensor includes multiple temperature sensors distributed around the printhead so as to provide a global measurement of the printhead temperature.

Claim 21 (previously added) The method of controlling the temperature of claim 12 wherein the pulse width calibration data is in the form of an equation.

Claim 22 (previously added) The method of controlling the temperature of claim 12 wherein the pulse width calibration data is in a look-up table.
